



Instrumentation Solutions for Hydrogen Applications

Components and systems for use with gaseous
and liquid hydrogen



ENGINEERING YOUR SUCCESS.

Contents

On-Board Vehicles - EC-79 Certified Components

Applications from 30 to 350 bar (435 - 5,076 psi)	6
Two Ferrule Tube Fittings - A-LOK® Series	6
Applications up to 700 bar (10,152 psi)	7
Medium Pressure Fittings - Cone and Thread - Autoclave Engineers®	7
Medium Pressure Needle Valves SM Series - Autoclave Engineers®	7
Medium Pressure Tubing - Autoclave Engineers®	7

ISO 19880-3 Certified Products for Hydrogen Refueling Stations

Medium Pressure Needle Valves 20SM Series - Autoclave Engineers®	8
Medium Pressure O-Ring Check Valves CXO Series - Autoclave Engineers®	8

General Hydrogen Applications

Applications up to 414 bar (6,000 psi).....	10
Two Ferrule Tube Fittings - A-LOK® Series	10
Ball Valves - B Series - Isolation and Directional Control Valves	10
Inline Filters - F Series	10
Check Valves - CO Series - Directional Control Valves.....	11
Stream Switching Systems - R-Max™ Gen II Series.....	11
Modular Sample Conditioning Systems - IntraFlow™ Series.....	11
Pressure Regulators - IR4000 and IR6000 Series.....	11
Excess Flow Shutoff Valves - FS190 Series.....	11
Applications up to 1,380 bar (20,000 psi).....	12
Medium Pressure Two Ferrule Inverted Tube Fittings - MPI™ Series	12
Medium Pressure Fittings - Cone and Thread - Parker Autoclave Engineers®	12
Permanent Ferrule-less Connectors - Phastite® Series	12
Ball Valves - Hi-Pro Series - Isolation Valves	12
Ball Valves - HB Series - Isolation Valves.....	12
Needle Valves MAN - MPI™ Series	13
Medium Pressure Needle Valves 15SM and 20SM Series - Autoclave Engineers®	13
Medium Pressure O-Ring Check Valves CXO Series - Autoclave Engineers®	13
Medium Pressure O-Ring Check Valves MAC - MPI™ Series	13
Double Block & Bleed Needle Type Manifold - 20DBNV Series - Autoclave Engineers®	13
Relief Valves - Soft Seat RVS Series - Autoclave Engineers®	14
Medium Pressure Tubing - MPI™ Series.....	14
Medium Pressure Actuators - Autoclave Engineers®	14
Medium Pressure Adapters - Autoclave Engineers®	14
Medium Pressure Accessories - Autoclave Engineers®	14

Cryogenic/LH₂ Applications

Globe Valves - Stainless Steel with Bronze Internals - Bestobell Industrial.....	16
Globe Valves - Stainless Steel - Bestobell Marine	16
Pneumatically Actuated Globe Valves - Stainless Steel with Bronze Internals - Bestobell Industrial.....	16
Pneumatically Actuated Globe Valves - Stainless Steel - Bestobell Marine	16
Lift Check Valves - Stainless Steel with Bronze Internals - Bestobell Industrial	17
Lift Check Valves - Stainless Steel - Bestobell Marine	17
Swing Check Valves - Stainless Steel - Bestobell Marine.....	17
Manual Gate Valves - Bestobell Industrial.....	17
Actuated Gate Valves - Pneumatic Tyre Design - Bestobell Industrial.....	17

WARNING

FAILURE, IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries or its authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

Offer of Sale

The items described in this document are available for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. Any sale contract entered into by Parker will be governed by the provisions stated in Parker's standard terms and conditions of sale (copy available upon request).

Your Reliable Partner for Driving the Energy Evolution Forward

Parker is supporting the global decarbonisation efforts through a broad range of solutions for a variety of applications. Our hydrogen-compatible components and systems enable safe and efficient operation from vacuum to 1,380 bar (20,000 psi) and temperatures from -253°C to +538°C (-423°F to +1000°F).

ON-BOARD VEHICLES

Two Ferrule Tube Fittings - A-LOK® Series EC-79 Certified

Parker Autoclave Engineers®:

Medium Pressure Fittings Tests Passed - Pending EC-79 Certification

Needle Valves - SM Series Tests Passed - Pending EC-79 Certification

Medium Pressure Tubing Tests Passed

**EC-79
CERTIFIED**

**ISO
19880-3
TESTED**

ISO-CERTIFIED PRODUCTS FOR REFUELING STATIONS

Parker Autoclave Engineers®:

Needle Valves - 20SM Series Tests Passed - Pending Certification

Check Valves - CXO Series Tests Passed - Pending Certification

GENERAL HYDROGEN APPLICATIONS

Two Ferrule Tube Fittings - A-LOK® Series

Permanent Ferrule-less Connectors - Phastite® Series

Ball Valves - B Series

Ball Valves - Hi-Pro Series

Ball Valves - HB Series

Inline Filters - F Series

Check Valves - CO Series

Stream Switching Systems - R-Max II

Modular Sample Conditioning Systems - IntraFlow™ Series

Pressure Regulators - IR4000 and IR6000 Series

Excess Flow Shutoff Valves - FS190 Series

CRYOGENIC/LH₂ APPLICATIONS

Bestobell Cryogenic Valves:

Globe Valves

Pneumatically Actuated Globe Valves

Lift Check Valves

Swing Check Valves

Manual Gate Valves

Actuated Gate Valves

GENERAL HYDROGEN APPLICATIONS

Parker Autoclave Engineers®:

Medium Pressure Fittings - Cone and Thread

Needle Valves - 15SM and 20SM Series

Check Valves - CXO Series

Double Block & Bleed Needle Type Manifold - 20DBNV Series

Relief Valves - RVS Series

Medium Pressure Accessories and Adapters

Medium Pressure Actuators


Medium Pressure MPI™ Series:

Fittings

Tubing

Needle Valves - MAN Series

Check Valves - MAC Series



VACUUM

1,380 BAR
20,000 PSI

Hydrogen can be very damaging to most metallic materials, causing embrittlement cracking. Follow this link to learn about the factors which can cause hydrogen embrittlement:
<https://discover.parker.com/Challenge-of-Hydrogen-Embrittlement-White-Paper>

READ WHITE PAPER | ▶

Stainless Steel material is Parker's standard offering for hydrogen systems and all the pressure and temperature ratings featured in this catalogue refer to this grade. Other materials are available on request.

Parker's range of tube fittings, needle valves and tubing for pressures up to 700 bar meet the general requirements of hydrogen components and systems used on hydrogen-powered motor vehicles as per regulation (EC) No 79/2009 of The European Parliament and of The Council of 14 Jan 2009.

Parker's needle valves 20SM series and check valves CXO series have successfully passed all the required tests for high pressure gas valves used in gaseous hydrogen stations of up to the H70 designation specified in ISO 19880-3 certification.

On-Board Vehicles

Components for on-board hydrogen-powered vehicles for pressures from 30 to 700 bar (435 to 10,152 psi).

EC-79 Certified

Parker's range of products approved for use on-board hydrogen-powered vehicles from 30 to 700 bar includes tube fittings, needle valves and tubing. These products meet the general requirements of hydrogen components and systems used on hydrogen-powered motor vehicles as per regulation (EC) No 79/2009 of The European Parliament and of The Council of 14 Jan 2009.

Applications from 30 to 350 bar (435 - 5,076 psi)



Two Ferrule Tube Fittings - A-LOK® Series EC-79 Certified

Parker A-LOK® two ferrule tube fittings are designed to achieve quality leak-free connections on-board hydrogen-powered vehicles up to 350 bar pressures and temperatures down to -40°C. These fittings provide reliable operation in cryogenic, pressure & thermal cycling and vibration applications. Manufactured at an IATF 16949 certified plant and EC-79 approved for hydrogen service, they come in a range of sizes and configurations in 316 Stainless Steel material. For optimised installation instructions see p.18 of this catalogue. To order EC-79 certified components, simply add the suffix EC79 at the end of your part number. For more details please see catalogue ref. 4190-FMTG.



Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1" (6mm to 25mm)*	350 bar (5,076 psi)	-40°C to +120°C (-40°F to +248°F)	Gas, Liquid	4190-FMTG

*A-LOK® tees and crosses approved in sizes up to 1/2" (12mm). Please contact Parker for further information.

Applications up to 700 bar (10,152 psi)



Medium Pressure Fittings - Cone and Thread - Autoclave Engineers® Tests Passed - Pending EC-79 Certification

Parker Autoclave Engineers medium pressure cone and thread connections are designed for applications that require higher flow rate capability. Manufactured from high tensile strength cold worked 316/316L Stainless Steel material as standard for 700 bar (10,152 psi) MAWP, this Medium Pressure range has all the benefits of the High Pressure version with all metal sealing for operations at temperatures from -40°C to +120°C (-40°F to +248°F). These fittings are designed for use with Parker Autoclave Engineers' 20SM Series valves and medium pressure tubing according to ASME B31.3 Chapter IX standards. To order EC-79 certified components, simply add the suffix EC79 at the end of your part number. For more details please see catalogue ref. 02-0124SE.

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	700 bar (10,152 psi)	-40°C to +120°C (-40°F to +248°F)	Gas, Liquid	02-0124SE



Medium Pressure Needle Valves SM Series - Autoclave Engineers® Tests Passed - Pending EC-79 Certification

Parker Autoclave Engineers SM Series valves are designed specifically for use with matching orifice medium pressure cone & thread fittings and tubing for the most efficient flow path possible using cone & thread style connections. They are manufactured using high tensile strength UNS S31600/S31603 cold worked 316/316L Stainless Steel material as standard for 700 bar (10,152 psi) MAWP. To order EC-79 certified components, simply add the suffix HYGEC79 at the end of your part number. For more details please see catalogue ref. 02-0112SE.

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	700 bar (10,152 psi)	-40°C to +120°C (-40°F to +248°F)	Gas	02-0112SE



Medium Pressure Tubing - Autoclave Engineers® Tests Passed

Parker Autoclave Engineers offers a complete selection of austenitic, cold drawn stainless steel tubing designed to match the performance standards of Parker Autoclave valves and fittings. Parker Autoclave Engineers medium pressure tubing is manufactured specifically for high pressure applications requiring both strength and corrosion resistance. For more details please see catalogue ref. 02-0124SE.

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	700 bar (10,152 psi)	-40°C to +120°C (-40°F to +248°F)	Gas, Liquid	02-0124SE



ISO Products For H₂ Refueling Stations

Components for hydrogen refueling stations for pressures up to 700 bar (10,152 psi).

Tests Passed, Pending ISO 19880-3 Certification

Parker's needle and check valves have successfully passed the required tests for high pressure valves used in gaseous hydrogen stations as specified in ISO 19880-3 certification. These are now awaiting the completion of the final steps towards achieving the certification.



Medium Pressure Needle Valves 20SM Series - Autoclave Engineers® Tested, Pending ISO 19880-3 Certification

These Parker Autoclave Engineers 20SM Series Needle Valves (HYG option) have unique STEM/SEAT and PACKING design that can withstand temperatures ranging between -73°C and 316°C and pressures of up to 700 bar (10,152 psi). The valves are available with two different styles of connection options including cone & thread and MPI™. To order ISO 19880-3 certified components, simply add the suffix HYG at the end of your part number. For more details please see catalogue ref. 02-0112SE.

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	700 bar (10,152 psi)	-73°C to +316°C (-99°F to +601°F)	Gas	02-0112SE



Medium Pressure O-Ring Check Valves CXO Series - Autoclave Engineers® Tested, Pending ISO 19880-3 Certification

These Parker Autoclave Engineers O-Ring Check Valves CXO Series (HYG option) can withstand temperatures ranging between -73°C and 316°C and pressures of up to 1,380 bar (20,000 psi). The valves are available with two different styles of connection options including cone & thread and MPI™. To order ISO 19880-3 certified components, simply add the suffix HYG at the end of your part number. For more details please see catalogue ref. 02-0124SE.

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	700 bar (10,152 psi)	-73°C to +316°C (-99°F to +601°F)	Gas	02-0124SE

Other associated products for hydrogen refueling stations are featured on the following pages.



General Hydrogen Applications

Components for general hydrogen applications at pressures from vacuum to 1,380 bar (20,000 psi).

Parker offers an extensive range of high-quality components and system solutions suitable for general hydrogen use in a wide variety of industries including power generation, petrochemical, agricultural and research & development.

Applications up to 414 bar (6,000 psi)



Two Ferrule Tube Fittings - A-LOK® Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/16" to 2" (2mm to 50mm)	414 bar (6,000 psi)*	-253°C to +538°C (-423°F to +1000°F)**	Gas, Liquid	4190-FMTG

* Please refer to Parker tube tables for higher pressure tube/fitting combinations up to 689 bar (10,000 psi).

** Material de-rating and media compatibility factors need to be taken into consideration for higher temperature applications. For optimised installation instructions see p.18 of this catalogue.



Ball Valves - B Series - Isolation and Directional Control Valves

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8" to 3/4" (3mm to 18mm)	414 bar (6,000 psi)	-54°C to +232°C (-65°F to +450°F)	Gas	4121-BV



Needle Valves - V Series - Isolation and Flow Control Valves

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8" to 3/4" (3mm to 18mm)	345 bar (5,000 psi)	-54°C to +232°C (-65°F to +450°F)	Gas	4110-NV



Inline Filters - F Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8" to 1" (3mm to 25mm)	414 bar (6,000 psi)	-51°C to +204°C (-60°F to +399°F)	Gas	4135-CV



Check Valves - CO Series - Directional Control Valves

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1/2" (6mm to 12mm)	414 bar (6,000 psi)	-57°C to +204°C (-71°F to +399°F)	Gas	4135-CV



Stream Switching Systems - R-Max™ Gen II Series

Available Size	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8"	34 bar (500 psi)	-57°C to +204°C (-71°F to +399°F)	Gas	4141-R



Modular Sample Conditioning Systems - IntraFlow™ Series

Available Size	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8"	34 bar (500 psi)	-57°C to +204°C (-71°F to +399°F)	Gas	4250



Pressure Regulators - IR4000 and IR6000 Series

Available Size	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4"	276 bar (4,000 psi)	-40°C to +260°C (-40°F to +500°F)	Gas	4255-PA



Excess Flow Shutoff Valves - FS190 Series

Available Size	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4"	241 bar (3,500 psi)	-23°C to +66°C (-9°F to +151°F)	Gas	4255-PA

Applications up to 1,380 bar (20,000 psi)



Medium Pressure Two Ferrule Inverted Tube Fittings - MPI™ Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	1,034 bar (15,000 psi)	-253°C to +538°C (-423°F to +1000°F)*	Gas, Liquid	4234-MA

* Material de-rating and media compatibility factors need to be taken into consideration for higher temperature applications.



Medium Pressure Fittings - Cone and Thread - Parker Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1 1/2"	1,380 bar (20,000 psi)*	-253°C to +538°C (-423°F to +1000°F)*	Gas, Liquid	02-0124SE

* Material de-rating and media compatibility factors need to be taken into consideration for higher temperature and higher pressure applications. Refer to technical catalogue 02-0142SE.



Permanent Ferrule-less Connectors - Phastite® Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1" (6mm to 25mm)	1,380 bar (20,000 psi)	-45°C to +93°C (-49°F to +199°F)	Gas	4235-PH



Ball Valves - Hi-Pro Series - Isolation Valves

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1" (6mm to 25mm)	689 bar (10,000 psi)	-54°C to +232°C (-65°F to +450°F)	Gas	4190-HBV



Ball Valves - HB Series - Isolation Valves

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/8" to 1/2" (6mm to 12mm)	489 bar (10,000 psi)	-54°C to +204°C (-65°F to +399°F)	Gas	4121-BV



Needle Valves MAN - MPI™ Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	1,034 bar (15,000 psi)	-73°C to +316°C (-99°F to +601°F)	Gas	4234-MA

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.



Medium Pressure Needle Valves 15SM and 20SM Series - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1 1/2"	1,380 bar (20,000 psi)*	-73°C to +316°C (-99°F to +601°F)*	Gas	02-0112SE

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.



Medium Pressure O-Ring Check Valves CXO Series - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	1,380 bar (20,000 psi)*	-73°C to +316°C (-99°F to +601°F)*	Gas	02-0124SE

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.



Medium Pressure O-Ring Check Valves MAC - MPI™ Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	1,034 bar (15,000 psi)	-73°C to +316°C (-99°F to +601°F)	Gas	4234-MA

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.



Double Block & Bleed Needle Type Manifold - 20DBNV Series - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 9/16"	1,380 bar (20,000 psi)*	-73°C to +316°C (-99°F to +601°F)*	Gas	02-9328SE

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.

* Material de-rating and media compatibility factors need to be taken into consideration for higher temperature and higher pressure applications. Refer to technical catalogue 02-0142SE.



Relief Valves - Soft Seat RVS Series - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
9/16"	1,380 bar (20,000 psi)	0°C to +204°C (32°F to +399°F)	Gas	02-0129SE

This valve has been modified for use with Hydrogen. To order, add the suffix HYG at the end of your part number.



Medium Pressure Tubing - MPI™ Series

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1"	1,034 bar (15,000 psi)	-253°C to +538°C (-423°F to +1000°F)	Gas, Liquid	4234-MA



Medium Pressure Actuators - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1 1/2"	1,380 bar (20,000 psi)	-73°C to +316°C (-99°F to +601°F)	Gas, Liquid	02-0121SE



Medium Pressure Adapters - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1 1/2"	1,379 bar (20,000 psi)	-253°C to +538°C (-423°F to +1000°F)*	Gas, Liquid	02-0127SE



Medium Pressure Accessories - Autoclave Engineers®

Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
1/4" to 1 1/2"	1,380 bar (20,000 psi)	-253°C to +538°C (-423°F to +1000°F)*	Gas, Liquid	02-0134SE

* Material de-rating and media compatibility factors need to be taken into consideration for higher temperature applications.



ADDITIONAL RESOURCES AVAILABLE ON WWW.PARKER.COM/IPD

- › WHITE PAPER - ADDRESSING THE CHALLENGE OF HYDROGEN EMBRITTLEMENT IN METALLURGY
- › BROCHURE - INSTRUMENTATION SOLUTIONS FOR HYDROGEN-POWERED VEHICLES
- › SMALL BORE EXPERT (SBEx) TRAINING ON SAFE INSTALLATION OF PRODUCTS

Cryogenic/LH₂ Applications

Components for cryogenic/LH₂ applications at temperatures down to -253°C (-423°F) and pressures up to 50 bar (725 psi).

Designed and engineered for use with Group 1 gases, Parker Bestobell's valves are suitable for liquid hydrogen applications requiring temperatures as low as -253°C. All valves are pressure-tested prior to dispatch.

To order, add the suffix -H at the end of your part number.



Globe Valves - Stainless Steel with Bronze Internals - Bestobell Industrial

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Soft	DN15 to DN100 (1/2" to 4")	Up to 50 bar (725 psi)	-253°C to +65°C (-423°F to +149°F)	Gas, Liquid	5190-BBV



Globe Valves - Stainless Steel - Bestobell Marine

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Metal to Metal	DN15 to DN100 (1/2" to 4")	Up to 50 bar (725 psi)	-253°C to +80°C (-441°F to +176°F)	Gas, Liquid	5190-BBM



Pneumatically Actuated Globe Valves - Stainless Steel with Bronze Internals - Bestobell Industrial

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Soft	DN15 to DN100 (1/2" to 4")	Dependent on end connections/ actuator	-253°C to +80°C (-423°F to +176°F)	Gas, Liquid	5190-BBV



Pneumatically Actuated Globe Valves - Stainless Steel - Bestobell Marine

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Metal to Metal	DN15 to DN100 (1/2" to 4")	Dependent on end connections/ actuator	-253°C to +80°C (-423°F to +176°F)	Gas, Liquid	5190-BBM



Lift Check Valves - Stainless Steel with Bronze Internals - Bestobell Industrial

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Soft	DN15 to DN100 (1/2" to 4")	Up to 50 bar (725 psi)	-253°C to +65°C (-423°F to +149°F)	Gas, Liquid	5190-BBV



Lift Check Valves - Stainless Steel - Bestobell Marine

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld Flange Class 150 and 300 	Soft	DN15 to DN100 (1/2" to 4")	Up to 50 bar (725 psi)	-253°C to +80°C (-423°F to +176°F)	Gas, Liquid	5190-BBM



Swing Check Valves - Stainless Steel - Bestobell Marine

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
Various Contact Parker	Soft	DN25 to DN80 (1" to 3")	Up to 50 bar (725 psi)	-253°C to +80°C (-423°F to +176°F)	Gas, Liquid	5190-BBM



Manual Gate Valves - Stainless Steel - Bestobell Industrial

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld 	Soft	DN40 to DN100 (1 1/2" to 4")	Up to 40 bar (580 psi)	-253°C to +65°C (-423°F to +149°F)	Gas, Liquid	5190-BBV



Actuated Gate Valves - Stainless Steel - Pneumatic Tyre Design - Bestobell Industrial

Available Connections	Seat Type	Available Sizes	MWP	Temperature	Hydrogen Form	Catalogue Ref. Number
<ul style="list-style-type: none"> Butt Weld Socket Weld 	Soft	DN40 to DN100 (1 1/2" to 4")	Up to 40 bar (580 psi)	-253°C to +65°C (-423°F to +149°F)	Gas, Liquid	5190-BBV

Appendix

A-LOK[®] tube fittings installation for hydrogen service

Parker has an improved and optimised installation procedure for its A-LOK[®] parts used in hydrogen service. Please follow the steps below for correct installation.

1. The tube should be fully inserted into the shoulder of the fitting until full tube abutment is achieved.
2. The nut should be advanced to the finger tight position and then be marked at the 6 o'clock position.
3. The nut should then be advanced 1 ½ turns with the appropriate wrench making sure a back-up wrench is used to hold the fitting body during the tightening process.
4. The mark will now be at the 12 o'clock position.

Once this has been achieved, the assembly will be ready to use in your Hydrogen system. For tube specifications, ordering information, preparation and pressure ratings, please refer to the Parker Fittings, Materials and Tubing Guide catalogue ref. 4190-FMTG.

Worldwide Division Headquarters

Europe, Middle East, Africa

AE – United Arab Emirates,

Dubai

Tel: +971 4 8127100

AT – Austria, St. Florian

Tel: +43 (0)7224 66201

AZ – Azerbaijan, Baku

Tel: +994 50 2233 458

BE/NL/LU – Benelux,

Hendrik Ido Ambacht

Tel: +31 (0)541 585 000

BY – Belarus, Minsk

Tel: +48 (0)22 573 24 00

CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00

CZ – Czech Republic,

Prague

Tel: +420 284 083 111

DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0

DK – Denmark, Ballerup

Tel: +45 43 56 04 00

ES – Spain, Madrid

Tel: +34 902 330 001

FI – Finland, Vantaa

Tel: +358 (0)20 753 2500

FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25

GR – Greece

Tel: +30 69 44 52 78 25

HU – Hungary, Budaörs

Tel: +36 23 885 470

IE – Ireland, Dublin

Tel: +353 (0)1 466 6370

IL – Israel

Tel: +39 02 45 19 21

IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21

KZ – Kazakhstan, Almaty

Tel: +7 7273 561 000

NO – Norway, Asker

Tel: +47 66 75 34 00

PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00

PT – Portugal

Tel: +351 22 999 7360

RO – Romania, Bucharest

Tel: +40 21 252 1382

RU – Russia, Moscow

Tel: +7 495 645-2156

SE – Sweden, Borås

Tel: +46 (0)8 59 79 50 00

SL – Slovenia, Novo Mesto

Tel: +386 7 337 6649

TR – Turkey, Istanbul

Tel: +90 216 4997081

UK – United Kingdom, Warwick

Tel: +44 (0)1926 317 878

ZA – South Africa, Kempton Park

Tel: +27 (0)11 961 0700

North America

CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

US – USA, Cleveland

Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

CN – China, Shanghai

Tel: +86 21 2899 5000

HK – Hong Kong

Tel: +852 2428 8008

IN – India, Mumbai

Tel: +91 22 6513 7081-85

JP – Japan, Tokyo

Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul

Tel: +82 2 559 0400

MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

SG – Singapore

Tel: +65 6887 6300

TH – Thailand, Bangkok

Tel: +662 186 7000

TW – Taiwan, Taipei

Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos

Tel: +55 080 0727 5374

CL – Chile, Santiago

Tel: +56 22 303 9640

MX – Mexico, Toluca

Tel: +52 72 2275 4200

European Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

